



Catalis

Packaging Technologies Pvt. Ltd.



➤ Altima series

Next-Gen High-Speed VFFS machine with stripping mechanism

- For packing chips, extruded snacks, etc.
- Six servo machine
- Stripping mechanism, greatly helps to reduce product on seal
- Simplest pulling mechanism with minimum moving parts
- The new easy to handle vertical seal unit with twin jaw mechanism, better seal strength & quality for BOPP laminate
- Vacuum pulling system, Ideal for BOPP laminate
- Advanced film splicing table
- Nitrogen monitoring and control station
- The new user friendly 10" touch screen

Catalis Packaging Technologies Pvt. Ltd.: 216, GIDC Makarpura, Vadodara-390010.

Mobile: +91 9825111747 | Email: info@catalispackaging.com | Web: www.catalispackaging.com



Catalis

Packaging Technologies Pvt. Ltd.

Specifications:

Model		CPT 325	CPT 425	CPT 525
Bag Type		Pillow Type Centre Sealed		
Mechanical speed		Maximum 120 bpm depend on product, bag size and filling system		
Min Bag Length		60 mm	70 mm	70 mm
Max Bag Length		275 mm	375 mm	375 mm
Min Film Width		110 mm	140 mm	240 mm
Max Film Width		325 mm	425 mm	525 mm
Bore of Film Roll core		3 inch		
Max Roll Diameter		400 mm		
Max Roll Weight		35 kg		
Product		Chips, Extruded Snacks, etc.		
Machine	Width	1055 mm	1130 mm	1255 mm
	Height	1746 mm	1880 mm	2096 mm
	Length	1855 mm	1895 mm	1995 mm
Power Supply Voltage		3 Phase, 415 VAC \pm 10%, 50 Hz		
Air Supply		2 CFM @ 6 bar		
Weight Approximately		1300 kg	1400 kg	1600 kg
Operational Temperature		0-40°C RH30-70% Non-Condensing		

All rights reserved. The information contain herein may be changed without prior notice.

Catalis Packaging Technologies Pvt. Ltd.: 216, GIDC Makarpura, Vadodara-390010.

Mobile: +91 9825111747 | Email: info@catalispackaging.com | Web: www.catalispackaging.com